

Monitoring Software for CANopen Slaves

CAN Dongle



CANopen Master Sim Datei Adresse Kommunik				 Hilf
	Bihl+Wiede	mann GmbH		
CAN Dongle Port	USB	Y		
Baudrate	500 kB	aud 💌		
Aktuelle Slave Addresse	3			
Bearbeiten 91	7 🔽 6 🗆	5 🗖 4 🔽	3 🗆 2 🗖 1 🗖	0 🔽
🗖 Ausgänge einfrieren			🔽 Kommunika	ation aktiv
Ausgangsdaten		Eingangsdat	en	
76543	210		76543210	
		13:51:07		
PD01 [0]: 2Fh 00101		PD01 [0]:	00h 0000000	
PD01 [1]: 07h 00000		PD01 [1]:	00h 0000000	
PD01 [2]: 00h 00000 PD01 [3]: 00h 00000		PD01 [2]: PD01 [3]:	00h 00000000	
PD01 [3]: 000 00000		PD01 [4]:	00h 0000000	
PD01 [5]: 00h 00000		PD01 [5]:	001 00000000	
PD01 161: 00h 00000		PD01 [6]:	00h 0000000	
	001 . 🔽	PD01 171:	00b 0000000	

The CANopen Master Simulator is an easy to use software for data exchange with CANopen slaves of many suppliers. The CANopen Master Simulator can exchange data with the slaves even without EDS-file. Input data can be read, output data can be written. Furthermore it is possible to read and write any object independent of the state of communication.

The CANopen Master Simulator offers the possibility to scan a

DeviceNet network and find all connected slaves. The digital I/O

data can be displayed binary, hexadecimal and also as ASCII code.

Analog I/O data are displayed decimal. The CANopen output data can be transmitted consistently to the CANopen slave.

The CANopen Master Simulator consists of the software and a CAN dongle. The CAN dongle is the ideal interface converter between the USB interface of a PC and CANopen. The converter needs for power supply only the USB interface. Therefore it is also suitable for mobile use with a laptop or a notebook.

Article no.	BW1453	
General data		
Name	CAN dongle	
Interfaces	USB interface	
	CAN interface with 9-pin D-sub-plug (male)	
Power supply	powered by the USB interface of the PC	
Length of connector cables	max. 2 m	
Transfer rates	5, 10, 20, 50, 100, 125, 250, 500 oder 1000 KBaud	
Installation		
Technical requirements	IBM compatible PC since 80486	
System requirements		
Operating system	Windows 98, Windows NT / Windows 2000, Windows Me / Windows XP / Windows 7 / Windows 10 (32 bit and 64 bit)	
Environment		
Operating temperature	0 °C +55 °C	
Storage temperature	-25 °C +70 °C	
Specification		
Specification	Software:	
	CANopen Master Simulator	
	CANopen dongle	

Accessories:

• D-Sub-data transmission cord for ASi Gateways with CAN interface