

Pluggable Screw Terminals for Modules in IP20

Compatible with COMBICON

Packing unit 100 pieces



Article no.	BW4882
General	
Packing unit	100 x pluggable screw terminals, 4 poles, black
Pitch	5 mm
Type of contact	sockets
Nominal cross section	2,5 mm ²
Rated voltage (III/2)	320 V
Nominal current	12 A
Conductor cross section	
Conductor cross section solid	0,2 ... 2,5 mm ²
2 conductors with same cross section, solid	0,2 ... 1,0 mm ²
Conductor cross section, flexible	0,2 ... 2,5 mm ²
2 conductors with same cross section, stranded	0,2 ... 1,5 mm ²
Conductor cross section, flexible, with ferrule	• without plastic sleeve: 0,25 ... 2,5 mm ²
	• with plastic sleeve: 0,25 ... 2,5 mm ²
2 conductors with same cross section, stranded, with ferrules	• without plastic sleeve: 0,25 ... 1,0 mm ²
	• with plastic sleeve: 0,5 ... 1,5 mm ²
2 conductors with same cross section, stranded, with TWIN ferrules	• with plastic sleeve: 0,5 ... 1,5 mm ²
AWG	24 ... 12
Stripped insulation length	7 mm
Tightening torque	0,5 ... 0,6 Nm