

24 Volt ASi-5/ASi-3 PROFINET Gateway

ASi-5 offers you many advantages and new possibilities like high data bandwidth, short cycle times and easy integration of IO-Link devices. To use ASi-5 slaves, all you need is a Bihl+Wiedemann ASi-5/ASi-3 gateway. It is now also available as a **low-cost 24-volt device for standard applications**.

The gateway is **particularly suitable for small applications** with few slaves. No additional ASi power supply is required because the gateway can be **supplied from 24 V directly from the control cabinet**. The integrated OPC UA server enables smooth and direct data transfer from the field level to Industry 4.0 applications.

Existing gateways can be replaced easily

In ASi networks without ASi-5 slaves, the new ASi-5/ASi-3 gateways act exactly as earlier Bihl+Wiedemann gateways because the ASi-3 part remains unchanged. Using our new gateways you can easily replace your existing gateways.



Fig.: 24 Volt ASi-5/ASi-3 PROFINET Gateway in Stainless Steel (BWU3847)

ASi-5/ASi-3 Gateways in Stainless Steel in detail:

- Compatible with existing networks
- 1.27 ms cycle time for up to 384 input and 384 output bits
- Cost-effective solution for all standard applications from Bihl+Wiedemann
- Integrated OPC UA server

ASi-5

**AUTOMATION
REINVENTED.**

**YOUR PATH
INTO THE
DIGITAL FUTURE.**



Questions about our products and solutions?

We would be happy to assist you.