

ASi-3 PROFINET Gateway in Stainless Steel

PROFINET IO

- offers IRT-technology
- 1 integrated Switch

Recognition of duplicate ASi addresses

ASi Earth Fault Detector integrated

ASi Noise Detector integrated

Optional Control III, programming in C



(figure similar)



Figure	Type	Model	Fieldbus interface ⁽¹⁾	Number of ASi networks, number of ASi Master ⁽²⁾	Integrated decoupling, ASi current measurement in the gateway ⁽³⁾	Diagnostic and configuration interface ⁽⁴⁾	Recognition of duplicate ASi addresses ⁽⁵⁾	ASi fault detector ⁽⁶⁾	Programming in C ⁽⁷⁾	Article no.
	PROFINET ASi	Gateway	PROFINET	2 ASi networks, 2ASi-3 masters	yes, max. 4 A/ASi network	Ethernet fieldbus	yes	yes	optional	BWU3363

(1) **Fieldbus interface**

Communication interface between fieldbus and gateway: interfaces for standardized fieldbus systems in industrial automation.
PROFINET ASi Gateway: interface for a PROFINET fieldbus

(2) **Number of ASi networks, number of ASi master**

"Double Master": 2 ASi networks, 2 ASi-3 masters.

(3) **Integrated decoupling, ASi current measurement in the gateway**

"yes, max. 4 A/ASi network": Data decoupling integrated in the gateway. Cost-effective power for 2 ASi networks with 1 power supply (optionally supply of multiple Single Gateways by 1 power supply). . Operation with short cable lengths with standard 24 V power supply possible.

(4) **Diagnostic and configuration interface**

"Ethernet fieldbus": Access to ASi Master and Safety Monitor with Bihl+Wiedemann software by using the Ethernet fieldbus interface.

The latest version of the device description file of the gateway is available in the "Downloads" section of the respective device.

(5) **Recognition of duplicate ASi addresses**

Detects whether the same address has been assigned to two ASi slaves. Frequent error when using a handheld addressing device.

(6) **ASi fault detector**

Checks the ASi line for interference effects such as noise, external voltages, ...

(7) **Programming in C**

Using a C-program offers the possibility to run mini-PLC functions with a gateway.

ASi-3 PROFINET Gateway in Stainless Steel

Article no.	BWU3363
Fieldbus interface	
Type	PROFINET 2 x RJ-45, integrated 2-Port-Switch, IRT capability
Baud rate	100 MBaud
Conformance Class	Class B integrated switch complies with Class C (IRT capability)
Function	PROFINET IO Device Media Redundancy Protocol (MRP) Shared Device
Card slot	Chip card (BW2222) for storage of configuration data
ASi	
ASi specification	ASi-3
Cycle time	150 μ s * (number of ASi-3 nodes + 2)
Operating voltage	30 V _{DC} (20 ... 31,6 V) (PELV voltage)
Operating current	ca. 250 mA
Current per ASi network	max. 4 A
ASi Power24V capability ⁽¹⁾	yes
Display	
LCD	menu, indication of ASi addresses, error messages in plain text
LED power (green)	power ON
LED PROFINET (green/red)	green: PROFINET communication active red: PROFINET communication not active
LED config error (red)	configuration error
LED U ASi (green)	ASi voltage o.k.
LED ASi active (green)	ASi normal operation active
LED prg enable (green)	automatic address programming enabled
LED prj mode (yellow)	in configuration mode
UL-specifications (UL508)	
External protection	An isolated voltage source with a PELV/SELV voltage \leq 30 V _{DC} must have internal or external current limiting
In general	UL mark does not provide UL certification for any functional safety rating or aspects of the above devices.
Environment	
Applied standards	EN 60529 EN 61000-6-2 EN 61000-6-4
Operating altitude	max. 2000 m
Operating temperature	0 °C ... +55 °C
Storage temperature	-25 °C ... +85 °C
Housing	Stainless Steel, for DIN rail mounting
Protection category	IP20
Tolerable loading referring to impacts and vibrations	according to EN 61131-2
Voltage of insulation	\geq 500 V
Weight	500 g
Dimensions (W / H / D in mm)	85 / 120 / 83

⁽¹⁾ **ASi Power24V**

The device can be operated directly on a 24 V (PELV) power supply. The gateway has been optimized with integrated data coupling coils and adjustable self-resetting fuses for safe use of powerful 24 V power supplies.

Article no.	BWU3363
Data decoupling integrated in the gateway	•
Current measurement of the ASi circuits	•
Self-resetting adjustable fuses	•
ASi earth fault monitor distinguishes between ASi cable and sensor cable	•
Cost-effective power for 2 ASi networks with 1 power supply	•

ASi-3 PROFINET Gateway in Stainless Steel

Accessories:

- Chip card, memory capacity 128 kB (art. no. BW2222)
- Bihl+Wiedemann Suite - Software for Configuration, Diagnostics and Commissioning (art. no. BW2902)
- Power supplies, e.g.: 30 V power supply, 4 A, 1 phase (art. no. BW4218), 30 V power supply, 8 A, 1 phase (art. no. BW4219), 30 V power supply, 8 A, 3 phases (art. no. BW4220), 30 V Power Supply, 16 A, 1 phase (art. no. BW4221), 30 V Power Supply, 16 A, 3 phases (art. no. BW4222) (for further power supply units visit www.bihl-wiedemann.de/en/products/accessories/power-supplies)
- PROFINET Master Simulator (art. no. BW3035, BW3057)
- Control III, Programming in C (art. no. BW2582)