


D-sub-data transmission cord for ASi Master in IP65, 1,5 m



ASi Master in IP65 (Specification 2.0)

| Clamps | PIN | Function | Colour |
|--------|-----|----------|--------|
| 1 | | PE | |
| 2 | | SHIELD | |
| 3 | 3 | BUS P | green |
| 4 | 8 | BUS N | yellow |
| 5 | 5 | GRND | blue |
| 6 | | PE | |
| 7 | | SHIELD | |
| 8 | | BUS P | |
| 9 | | BUS N | |
| 10 | 6 | +5 V | red |


| Article no. BW1097 | |
|------------------------------------|----------------------------|
| Connection | RS 485 prefabricated cable |
| Storage temperature | -40°C ... +85°C |
| Operating temperature | -25°C ... +60°C |
| Protection category (IEC) EN 60529 | connector IP65, plug IP20 |
| Dimensions (L, W, H) | ca. 50 mm, 20 mm, 30 mm |
| Length | 1,5 m |

D-sub-data transmission cord 9-pin, 1,8 m



| Article no. BW1058 | |
|----------------------------|----------------------------|
| Connection | D-Sub plug D-Sub socket |
| Length | 1,8m |
| PIN 1 connected with PIN 1 | |

D-sub-data transmission cord for ASi Gateways with CAN interface



ASi/CAN Gateway

| Clamps | PIN | Function | Colour |
|--------|-----|----------|--------|
| 1 | | n.c. | |
| 2 | 7 | CAN_H | white |
| 3 | | SHIELD | |
| 4 | 2 | CAN_L | brown |
| 5 | | n.c. | |

| Article no. BW1226 | |
|------------------------------------|-------------------------------------|
| Connection | D-subsocket, 5-pin COMBICON plug |
| Operating temperature | -40°C ... +85°C |
| Storage temperature | -25°C ... +60°C |
| Protection category (IEC) EN 60529 | IP20 |
| Dimensions (L, W, H) | ca. 50 mm, 20 mm, 30 mm |
| Length | 1,5 m |

ASi addressing cable (with COMBICON connector) for direct addressing with ASi master



| Article no. BW2324 | |
|--------------------|---|
| Connection | round connector 2-pin COMBICON-connector |
| Length | 1,5 m |
| Connector (Master) | + ASi - |

ASi addressing cable - infrared addressing adapter



| Article no. BW1935 | |
|--------------------|-----------------------------|
| Connection | infrared head/M12 connector |
| Length | 1 m |

ASi addressing cable for addressing with handheld address programming device



| Article no. BW3304 | |
|---|--------------------------|
| Connection | ASi profile cable to M12 |
| Length | 1,0 m |
| scoop of delivery incl. 2 x substructure modules 60 mm x45 mm | |

ASi addressing cable for direct addressing with ASi master



| Article no. BW3305 | |
|---|-------------------------------|
| Connection | ASi profile cable to COMBICON |
| Length | 1,0 m |
| scoop of delivery incl. 2 x substructure modules 60 mm x45 mm | |

Connecting cable (Module/programming device)



| Article no. BW1802 | |
|--------------------|---|
| Connection | round connector 2-pin/ M12 connector |
| Length | 1,6 m |

Addressing plug



| Article no. BW3340 | |
|--------------------|----------|
| Color | black |
| Packing unit | 5 pieces |

Protection cap for not used M12 sockets, IP67



| Article no. BW2368 | |
|--------------------|-----------|
| Color | blue |
| Packing unit | 50 pieces |

Protection cap for ASi-5 addressing socket, IP67, M12



| Article no. BW4056 | |
|--------------------|-----------|
| Color | blue |
| Packing unit | 50 pieces |

Memory plug cover



| Article no. BW3155 | |
|--------------------|---------|
| Color | blue |
| Packing unit | 1 piece |

Cross-Link-cable for ASi/Ethernet Gateway



| Article no. BW1304 | |
|--------------------|--|
|--------------------|--|

Serial cable for ASi Masters and ASi Monitors in stainless steel



| Article no. | BW1575 |
|-------------|--|
| Connection | D-Sub data cable 9-pin, Mini-Din plug 6-pin |
| Length | 1,8 m |

USB connector cable for Safety Basic Monitor




| | |
|--------------------|------------------------|
| Article no. | BW2530 |
| Connection | USB type A – Micro USB |
| Length | 1,8 m |
| Color | black |

ASi Probe



Article no. BW1745

Chip card for Bihl+Wiedemann ASi products



BW2079/BW2222



BW4055

| Article no. | BW2079 | BW2222 | BW4055 |
|---|---------------------|-----------------------|-----------------------|
| Memory capacity | 32 kByte (256 kbit) | 128 kByte (1024 kbit) | 512 kByte (1024 kbit) |
| Weight | approx. 1 g | | |
| Dimensions (L / W / H in mm) | 25 / 15 / 1 | | |
| Accessories: | | | |
| <ul style="list-style-type: none"> • BW2079 for all ASi-3 Standard and all ASi-3 Safety products with chip card by Bihl + Wiedemann. • BW2222 for ASi-3 Safety Monitors and ASi-3 Gateways in Stainless Steel Safety Version 4.X (for maximum 4 Safety configurations on a chip card). • BW4055 for Gateways supporting ASi-5 | | | |

Memory Plug for Bihl+Wiedemann ASi products



| | |
|---|---------------------|
| Article no. | BW3241 |
| Memory capacity | 32 kByte (256 kbit) |
| Weight | approx. 2 g |
| Dimensions (L / W / H in mm) | 26,5 / 7 / 4,5 |
| Packing unit | 10 pieces |
| Accessorie for BW3064 ASi Safety Output Module (M12), IP67 | |